



1621 : Threading Machine 4"



The + product :

Automatic opening threading head.

Quick, simple thread size adjustment.

Hammer-type chuck and long jaws to rapidly, firmly and safely secure the pipe.

Description

Machine producing "gas" threads with sealing as per NFE 03.004 compliant with ISO/7.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

Self-priming gear-style oil pump.

Raised strainer avoids oil contamination by iron filings.

Variable oil flow control.

Heavy-duty dies available in HSS and standard grade steel.

Slotted dies for quick and easy replacement without removing the head.

3 gears for optimum cutting and threading of each pipe diameter.

Safety pedal for starting and stopping the machine.

Three-blade reamer for a precision result.

Special storage compartment.

A machine of proven endurance, designed for high-volume applications.

More Information

Capacity	Steel: BSPT, NPT Ø 1/4" - 4". BSPP Ø 1/2" - 2". Stainless steel: BSPT, NPT Ø 1/4"- 4".
Conseils	Use specially-designed dies and cutting wheels when working with zinc-coated and stainless steel.
Supplied with	<ul style="list-style-type: none">- 1 automatic 1/2" to 2" BSPT threading head,- 1 automatic 2.1/2" to 4" BSPT threading head,- 1 set of right-hand BSPT dies 1/2" - 3/4",- 1 set of right-hand BSPT dies 1" - 2",- 1 set of right-hand BSPT dies 2.1/2" - 4",- 1 steel pipe cutting wheel,- 2 x 5 L synthetic threading oil (ref. 110605),- 4 support legs,- 1 safety pedal.

References

SKU	Composition	Size mm	Motor	Dies	Power W	Speed rpm	kg
162140	Ø": 1/2 - 3/4, 1 - 2, 2.1/2 - 4. Ø mm: 8/13 - 12/17, 26/34 - 50/60, 66/76 - 102/114	1200 x 870 x 1200	Single-phase induction 230 V motor	Right-hand BSPT	1600	36/20/11	142,200

