TAG's E-Z Curve Series is a portable oxy-fuel hand held oxy-fuel cutting machine with an integrated drive system, ignition device and Start-Stop-function for pre-heating flame. It ensures highest cut quality in vertical, circular and shape cutting as well as bevelling.

Besides cutting of flat surfaces it is also possible to perform curved contours on vertical surfaces like H-beams, pipes and bended plates. Thanks to the low weight of 3.5kg E-Z Curve Series can be used as simple as an ordinary hand cutting torch. TAG's E-Z Curve Series comes with auto ignition, one click gas shut off, flame pre-set valves.

Standard all positions drives

High efficiency performance the drive switch is linked to the cutting oxygen valve causing simultaneous operation of cutting oxygen and drive power. Cutting attachments quickly changed for all types of cutting applications.

E-Z Curve TAG kit

The E-Z Curve TAG kit is a complete kit that will give the operator a variety of cutting options and solutions for optimal performance and comes standard with the following items:

- E-Z Curve body including universal nozzle-mix torch suitable for all nozzle-mix cutting nozzle
- Small circle cutting attachment 30 120mm
- Bevel cutting attachment variable up to 45 Degree
- Straight cutting attachment
- Guide lever
- AC adaptor with cable
- Cutting nozzles up to 30mm
- Standard tool set
- Steel carrying case







TECHNICAL SPECIFICATION	
Part No	EZCTK
Power Supply	AC 100-240V
Cutting thickness	5 - 30mm
Cutting speed	150 - 530mm/min
Ignition	Automatic ignition
Torch	Universal nozzle-mix torch suitable for all nozzle-mix cutting nozzle
Cut/Bevel Angle	Straight, circle and bevel cutting variable up to 45 Degree
Weight	3.5kg / 7.7lbs
Length	Total length 550mm

Scope of Delivery

E-Z Curve body including universal nozzle-mix torch suitable for all nozzle-mix cutting nozzle

Small circle cutting attachment 30 - 120mm

Bevel cutting attachment variable up to 45 Degree

Straight cutting attachment

Guide lever

AC adaptor with cable Cutting nozzles up to 30mm Standard tool set Steel carrying case **Operation Instructions**







