Cordless magnetic drilling machine

EBM.360

Technical data

| | Metric | Imperial |
|--|----------------------|---------------------------|
| Annular cutting | Ø 12 - 36 mm | Ø 1/2" - 1 7/16" |
| Twist drilling | Ø 1 - 13 mm | Ø 1/16" - 1/2" |
| Countersinking | Ø 10 - 40 mm | Ø 3/8" - 1 9/16" |
| | | |
| Length | 297 mm | 11 11/16" |
| Width | 112 mm | 4 7/16" |
| Height | 420 - 610 mm | 16 9/16" - 24" |
| | | |
| Stroke | 230 mm | 9 1/16" |
| Weight (incl. batt)* | 11.7 kg | 25.8 lbs |
| Magnet (I x w x h) | 160 x 80 x 42 mm | 6 5/16" x 3 1/8" x 1 5/8" |
| Magnetic force | 1,700 kg | 3,750 lbs |
| Motor power | 1,300 W DC | 35.1 A DC |
| Total power | 1,350 W DC | 36.5 A DC |
| Speed (no load) | 506 rpm | |
| Speed (load, 1,300 W, 35.1 A DC) 375 rpm | | |
| Spindle (Weldon) | 19.05 mm | 3/4" |
| Battery capacity | 37 V / 2.6 Ah Li-ion | |

From 0% to 75% battery charge in 17 minutes! Battery charge 75% to 100% takes 58 minutes. Fully charged in 75 minutes.



Benefits:

* Without handles

- Powerful battery with charger
- Powerful high-torque DC motor
- Multi-level electronic protection for optimal safety
- Extremely short battery charging time
- Detachable spindle and integrated tool cooling and lubrication
- High-precision height adjustment for:
 - Low maintenance
- Minimal wear correction
- Strong dual coil CNC machined magnet

