

**Description****Upper** : No-Sew Breathable and Resistant Fabric**Lining** : Breathable Lining**Midsole** : Textile Anti-Perforation Midsole**Toe-Cap** : Extra Light Fiber Glass Toe Cap**Footbed** : Comfortable Removable Anatomical PU Footbed**Outer Sole** : Resistant and Antislip PU Outer Sole**Oil and Hydrocarbon Resistant Sole** : Yes**Metal Free** : Yes**Water Resistant Upper** : Yes**ESD** : Yes**Carton packing** : 10 Pairs/ Carton**Packing**× 1
Pair× 10
Boxes10
Pairs / Carton**Features**

- Metal-free construction for maximum flexibility and lightweight comfort
- S3L protection with textile anti-perforation midsole against sharp objects
- Fiberglass toe cap for high-impact protection without added weight
- Advanced anti-abrasion upper for extended durability in demanding environments
- Reinforced toe & heel areas for enhanced wear resistance
- Slip-resistant outsole (SR) for superior grip on ceramic and steel surfaces
- ESD certified to safely dissipate electrostatic charges
- Fuel oil resistant outsole (FO) for industrial environments
- Ergonomic PU insole for long-lasting cushioning and all-day comfort

SKU/Reference	Size	Carton (L×W×H) m	Carton Weight	EAN13	HS Code	Country of origin
APULLY36	36	0.62 × 0.44 × 0.35	12.38 kg	7630048226365	64034000	China
APULLY37	37	0.62 × 0.44 × 0.35	12.47 kg	7630048226372	64034000	China
APULLY38	38	0.62 × 0.44 × 0.35	13.05 kg	7630048226389	64034000	China
APULLY39	39	0.6 × 0.42 × 0.35	13.6 kg	7630048226396	64034000	China
APULLY40	40	0.37 × 0.65 × 0.47	14.5 kg	7630048226402	64034000	China
APULLY41	41	0.62 × 0.44 × 0.34	14.07 kg	7630048226419	64034000	China
APULLY42	42	0.37 × 0.65 × 0.47	15 kg	7630048226426	64034000	China
APULLY43	43	0.37 × 0.65 × 0.47	15.26 kg	7630048226433	64034000	China
APULLY44	44	0.66 × 0.46 × 0.37	15.63 kg	7630048226440	64034000	China
APULLY45	45	0.66 × 0.47 × 0.37	16.06 kg	7630048226457	64034000	China
APULLY46	46	0.66 × 0.47 × 0.37	15 kg	7630048226464	64034000	China
APULLY47	47	0.65 × 0.47 × 0.38	16.94 kg	7630048226471	64034000	China

StandardsEN ISO 20345: 2022
S3L SR FO ESD

CAT.II