

CUT 35GDW

DIGITIZED WIDE INPUT VOLTAGE NON-HIGH FREQUENCY

TECHNICAL ADVANTAGES

- Non-HF, non-contact arc striking.
- PFC function.
- Wide input voltage from 85V-265V.
- Able to grid cutting.
- Compact and portable.
- Recommended quality cutting thickness: 6mm; Max. cutting thickness is 12mm (carbon steel);



STANDARD ACCESSORY



Trachea,3m	Quick coupling	Throat hoop
1PCS	1PCS	4PCS

• Plate: 3mm carbon steel plate



• Plate: 12mm carbon steel plate

TECHNICAL PARAMETER

Input voltage (V)	Frequency (Hz)	Rate input current (A)	No-load voltage (V)	Current Range (A)	Rate output voltage (V)	Efficiency
AC115V±15% AC230V±15%	50/60	AC115V±15%:23 AC230V±15%:20	200	AC115V±15%:15-25 AC230V±15%:15-35	AC115V±15%:90 AC230V±15%:94	80%
Power factor	Arcing Way	Pressure of air compressor(Kgf/cm2)	Limited cutting thickness (mm)	Recommended cutting thickness (mm)	Weight (kg)	Dimensions L*W*H (mm)
0.99	Contact	3.5-4.5	12	1-8	5.5	315*135*250