



FYP-1319



FYP-1924



FYP-2432



FYP-3241



FYP-4150



FYP-5060/FYP-6075

技术参数 Technical Parameters

产品名称 Product Name	型号 Model	螺钉范围 Bolt Range (mm)	六角螺母范围 Nut Range (mm)	工作能力 Output (ton)	重量 Weight (kg)
螺母破切器系列 Screw Cutter	FYP-1319	M6-M12	13-19	5	3
	FYP-1924	M12-M16	19-24	10	4
	FYP-2432	M16-M22	24-32	15	6
	FYP-3241	M22-M27	32-41	20	8
	FYP-4150	M27-M33	41-50	35	10
	FYP-5060	M33-M39	50-60	50	12
	FYP-6075	M39-M48	60-75	90	35



产品说明

1. 适于维修、检修、测试和阀门更换应用。
2. 整体分离楔概念：无摩擦，平行平常运动。
3. 消除法兰损伤和分离楔损坏的危险。
4. 独特的互锁楔子设计—第一级无弯曲无滑脱危险。
5. 插入口要求尺寸仅为6mm。
6. 台阶形张臂的设计使每格台阶可承受满负荷。
7. 较少的运动部件，经久耐用，维护方便。

Product Description

1. Suitable for maintenance, overhaul, testing, and valve replacement Ying Yong.
2. As a whole wedge of the concept of separation: no friction, parallel movement usually.
3. To eliminate separation wedge flange damage and the risk of damage to.
4. Unique interlocking wedge design—first-class non-bending risk of non-slip.
5. Insert l l asked measuring only 6mm.
6. Stepped Zhang arm design so that each cell can withstand full load step.
7. Less moving parts, durable, easy to maintain.

型号Model	FS-14
加工能力Processing Capacity	14T
顶部间隙Top Clearance	6mm
最大分离厚度 Maximum Separation Thickness	81mm
分离类型Type Of Separation	液压 Hydraulic
重量Weight	9.5kg
油量Oil Volume	78mm <sup>3</sup>



型号Model	FSH-14
加工能力Processing Capacity	14T
顶部间隙Top Clearance	6mm
最大分离厚度 Maximum Separation Thickness	81mm
分离类型Type Of Separation	液压 Hydraulic
重量Weight	7.1kg
油量Oil Volume	78mm <sup>3</sup>



型号Model	YQ-55
加工能力Processing Capacity	12T
顶部间隙Top Clearance	11mm
最大分离厚度 Maximum Separation Thickness	60mm
分离类型Type Of Separation	手动液压 Manual hydraulic
重量Weight	6.5kg
油量Oil Volume	78mm <sup>3</sup>